


Service  
Service  
Service



43 152 A12

# Service Manual

COMPACT  
disc  
DIGITAL AUDIO

## TABLE OF CONTENTS

Exchange instruction for optical pickup unit  
Partslist  
Service hints  
Cleaning the lens

Safety regulations require that the set be restored to its original condition and that parts which are identical with those specified be used.

**CLASS 1  
LASER PRODUCT**



## Exchange instruction for the OPTICAL PICKUP unit

### WARNINGS: Danger of electrostatic discharge!

The laser diode is more sensitive to ESD than MOS ICs.

Therefore take care of ESD-protection whenever working on the disc drive.

Never touch the lens!



### Exchanging the optical pickup unit

- 1) Remove fixing spring of guiding axes.
- 2) Lift guiding axes so far that gear gets out of engagement.
- 3) Pull the pickup unit off the axes.
- 4+9) Pull off the connectors as shown in the sketch and plug them on the new pickup unit.
- 5+6) Remove the toothed bar plus compression spring.
- 7+8) Mount toothed bar and compression spring on new pickup unit.
- 10) Put the new pickup unit on the guiding axes.
- 11) Put guiding axes down to the chassis while positioning the pickup unit so that gear is forced easily into engagement.
- 12) Mount fixing spring of guiding axes.

#### IMPORTANT NOTE:


All electrical adjustments have to be carried out new. Follow the adjustment table of the service manual for the relevant set the disc drive is used. The laser control is located on the optical pickup unit. The laser current has therefore already been adjusted by the factory.

4822 691 20768 RCD1.2D disc drive assy

- |   |                |                      |
|---|----------------|----------------------|
| 4 | 4822 522 32451 | gear wheel           |
| 6 | 4822 522 32453 | toothed bar          |
| 7 | 4822 492 51979 | spring, compression  |
| 8 | 4822 492 63941 | spring, wire (motor) |
| 9 | 4822 492 63942 | spring, wire (axes)  |

- |      |                |                          |
|------|----------------|--------------------------|
| 1001 | 4822 691 30327 | optical pickup unit      |
| 1003 | 4822 361 21113 | servomotor, RF300C-11440 |
| 1004 | 4822 276 12163 | switch, leaf             |

Only those parts of which a service code number is stated are service parts.



# Service Manual

Published by Consumer Electronics Printed in The Netherlands © Copyright reserved Subject to modification

4822 725 25111



# PHILIPS

PCS 63 873

## SPECIFICATION

### GENERAL

Mains voltage	: 230V - /00/20 240V - /05 120V - /37 120V/230V -/21/41
Mains frequency	: 50Hz - /00/05 60Hz -/17 50/60Hz -/21/41
Battery	: 9V (R20 x 6)
Power consumption	: 24W max.
Dimension (W x D x H)	: 420 x 180 x 229mm
Weight	: 3.7kg

### TUNER : FM SECTION

Tuning range	: 87.5MHz - 108MHz
IF frequency	: 10.7MHz
Sensitivity at 26dB S/N	: < 23 $\mu$ V
Selectivity at 600kHz bandwidth	: > 20dB
IF rejection	: > 50dB
Image rejection	: > 20dB

### TUNER : AM SECTION -/00/05/20/21/41

Tuning range	MW : 522kHz - 1607kHz LW : 148.5kHz - 284kHz – not for /21/41
IF frequency	: 468kHz
Sensitivity at 26dB S/N	MW : < 4.0mV/M LW : < 6.0mV/M – not for /21/41
Selectivity at 18kHz bandwidth	MW : > 16dB LW : > 20dB – not for /21/41
IF rejection	MW : > 24dB LW : > 26dB – not for /21/41
Image rejection	MW : > 28dB LW : > 30dB – not for /21/41

### TUNER : AM SECTION -/37

Tuning range	AM : 530kHz - 1710kHz
IF frequency	: 468kHz
Sensitivity at 26dB S/N	AM : < 4.0mV/M
Selectivity at 18kHz bandwidth	AM : > 16dB
IF rejection	AM : > 24dB
Image rejection	AM : > 28dB

### AMPLIFIER

Output power at 10% distortion:	Mains : 2 x 1.6W -1dB Battery : 2 x 1.6W -1dB
Speaker impedance	: 2 x 6 $\Omega$
Frequency response within +7dB/-3dB	: 100Hz - 8kHz

### CASSETTE RECORDER

Number of tracks	: 2 x 2 stereo
Tape speed	: 4.76 cm/sec $\pm$ 3%
Wow and flutter	: < 0.3%
Fast-wind time C60	: 120 sec
Bias system:	AM/FM : 60kHz $\pm$ 3kHz
Recording playback frequency response within -8dB	: 250Hz - 6.3kHz
Signal to Noise ratio:	AM/FM rec : > 40dB

### COMPACT DISC

Frequency response within $\pm$ 3dB	: 30Hz - 160kHz
Signal/Hiss ratio	: > 80dB
Distortion at 1kHz	: < 0.3%
Channel difference at 1kHz	: < 2dB
Channel crosstalk at 1kHz	: 50dB



## SERVICE HINTS

### Service DISC - HOLDDOWN

The disc must always be fixed well on the turntable.  
If the mechanism has to be dismantled for repair, a separate disc-holddown has to be used ( e.g. service disc-holddown 4822 532 51871 ).  
The CD mechanism then can function normally as in the set.

### CHARACTERISTIC FAILURES

#### Possible customer complaint:

- no function, does not startup
- plays badly
- skips tracks
- very sensitive to shocks

#### General observation by investigation:

HF- signal too small.

**Cause:** Mechanical x/y-adjustment of the diode array on the optical pickup unit has drifted.

**Attention:** The laser control of the RCD1.2 disc drive is located on the optical pickup unit. The laser current has been adjusted in the production line and is **not** intended to be **varied for service purposes**.

If the HF - signal is considerably smaller than 800mV<sub>pp</sub>, check as follows:

- \* Play a disc.
- \* Turn the *FOCUS OFFSET* potmeter while observing the HF - signal:
  - THE HF - SIGNAL DECREASES IN BOTH DIRECTIONS  
→ the x/y-adjustment of the diode array is o.k.
  - THE HF - SIGNAL INCREASES IN ONE DIRECTION  
→ adjust to max. HF signal level and check

*FOCUS OFFSET* voltage:

$\leq \pm 100\text{mV DC}$  → x/y-adjustment of diode array within tolerance.

$> \pm 100\text{mV DC}$  → x/y-adjustment of diode array has drifted and is out of tolerance.

→ **exchange optical pickup unit!**

In case of a positive result — x/y-adjustment of diode array is o.k. — the reason for a too small HF signal might be a dying laser diode or any other fault in the electronic circuit.

### REDUCTION of REPAIR PRICE

If the disc drive does not function, in most cases the optical pickup unit will be defect.

To reduce the actual repair price it is recommended to replace the optical pickup unit only.

Follow the exchange instruction on the previous page.

### CLEANING the LENSE

**Principle: Avoid cleaning of the lens !**


**DUST particles** are normally no major problem. They can be blown away with oilfree compressed air.

#### Finger - prints

If the lens is obviously polluted with finger - prints, it can be cleaned with alcohol or spirit.

Take a padstick and tip it into alcohol until it is soaked. Then clean the surface of the lens by rotating the soaked padstick smoothly.


The alcohol will dissolve the finger - prints, rotation helps mechanically. Finally the lens will be filled with the dirty cleaning solvent.



Now incline the lens ( disc drive ) and soak the solvent up with absorbent paper.

The remnants of the solvent will evaporate.

absorbent paper



## Service Aids

### Screw drivers:

Torx driver set T6 - T20	4822 395 50145
Torx driver T8	4822 395 50263
Torx driver T10 extended	4822 395 50423

### Cassettes:

SBC 420 Test cassette Ferro - IEC 14822 397 30071

### Compact disc:

SBC 429 Audio Signals disc 1 4822 397 30184





## Service Hints


Align the Mode Selector switch (item no. 1550) and Mode Switch ④ to the left before encasing the Front cabinet to the Back Cabinet.

## CD SERVICE MODE

Following can be tested with test programme.

- \* Sledge motor
- \* Disc motor
- \* Focus servo

Operation Sequence	Display Shows	Remarks	In case of problem
Step 0 Hold "Next" & "Previous" while switching mode selector to "CD"		Sledge servo can be moved inward or outward by pressing "Previous" or "Next" respectively. Sledge move till key is released. Pressing "Shuffle" moves Discmotor clockwise. Pressing "Stop" moves Discmotor anti-clockwise. Discmotor turn till key is release.	Sledge motor and drive circuit for sledge motor. Disc motor and driver circuit for disc motor.
Step 1 Insert any disc. Close the door.  Press "Play".		Focus on.	Focus servo circuit.
Step 2 Press "Play"		Disc motor on.	Disc motor and driver circuit for disc motor.
Step 3 Press "Play"		Radial Servo on. Mute is release. Holding "Next/Previous" key jump in small step. Holding "Shuffle/Play" key moves fast in/outside.	
From anywhere within the service program. Press "Stop" to get back to step 0. To leave service mode, switch selector to OFF position.			



### Connections and Controls

- |   |                        |      |
|---|------------------------|------|
| ① | Button Sets - Cassette |      |
| ② | CD/Cassette Door       |      |
| ③ | Button Sets - CD       |      |
| ④ | Mode Switch            | 1550 |
| ⑤ | Thumbwheel - Tuning    |      |
| ⑥ | Band Switch            | 1102 |
| ⑦ | Volume Knob            | 3500 |

### TAPEDECK ADJUSTMENT


ADJUSTMENT	CASSETTE	SK . . .	TAPEDECK POSITION	MEASURE ON	READ ON	ADJUST WITH	ADJUST TO
Azimuth	10kHz SBC 420 *	Cass.	Play	* 1	mv-meter	Left hand Screw R/PB Head	Max.
Motor Speed	3150Hz SBC420 *	Cass.	Play	* 1	Wow and Flutter Meter	Preset in motor	** a

\* SBC 420 : 4822 397 30071


\*\* a The maximum permissible speed deviation is 3%.  
Moreover, the wow and flutter value can be read.  
This value should not exceed 0.3%.

\* 1 Connected across the speaker terminals


DISASSEMBLY DRAWING



# BLOCK DIAGRAM



# WIRING DIAGRAM




# FOR AZ8140 ONLY

⊕ PART OF TAPE DECK ASSY FOR AZ8140



## TUNER CIRCUIT DIAGRAM - FM/LW/MW



# ALIGNMENT

SK...	FREQUENCY	I/P	VARICON	ADJUST	O/P	SCOPE/METER
-------	-----------	-----	---------	--------	-----	-------------

## AM - IF

MW *	468kHz via 10nF	A	min.	5110 5109	1	<div> <div></div> <div></div> <div></div> </div> max.
------	--------------------	---	------	--------------	---	---

## AM - RF

MW *	512kHz	B	max.	5108	1	<div> <div></div> <div></div> <div></div> </div> max.
520 - 1605kHz	1635kHz		min.	C4		
	550kHz		Tune	5113		
	1500kHz		Tune	C3		
LW *	147kHz	B	max.	5107	1	<div> <div></div> <div></div> <div></div> </div> max.
148.5 - 283.5kHz	291kHz		min.	2123		
	155kHz		Tune	5114		
	270kHz		Tune	2108		

## FM - RF

FM 87.5-108MHz (64.7-108.5MHz)	87.35MHz @ (64.7MHz)	C	max.	5102	1	<div> <div></div> <div></div> <div></div> </div> max.
	108.25MHz @ (108.5MHz)		min.	C2		
	88MHz @ (68MHz)		Tune	5101		
	106MHz @		Tune	C1		

\* Mod. 400Hz 30% ( ) For extended FM @ ± 0.15MHz

## STEREO DECODER


SK...	FREQUENCY	I/P	VARICON	ADJUST	O/P	SCOPE/METER
FM STEREO	98MHz §	C	Tune	3108	D	<div> <div></div> <div></div> <div></div> </div> 152±0.1kHz

§ Without Pilot


Repeat



# TUNER COMPONENT LAYOUT - FM/LW/MW



1101 A 2	9101 C 2
2101 B 2	9103 A 2
2102 D 1	9105 A 1
2103 D 1	9108 A 2
2105 C 1	9109 B 1
2106 C 1	9111 C 1
2107 B 1	9112 A 2
2108 B 1	9113 B 2
2111 B 1	9115 C 2
2114 C 2	9116 C 2
2115 B 2	9118 C 1
2116 B 2	9120 B 2
2120 D 2	9121 A 1
2121 D 2	9122 C 1
2122 D 2	9123 D 1
2123 A 2	9124 C 1
2127 A 2	
2130 A 1	
2133 D 2	
2134 D 2	
2135 D 2	
2136 D 1	
2137 D 1	
2138 D 1	
2139 C 1	
2140 C 2	
2141 D 2	
2142 D 1	
2146 A 1	
2149 A 1	
2150 A 2	
3106 D 2	
3107 B 2	
3108 C 2	
3110 D 1	
3111 D 1	
3112 D 2	
3113 A 1	
3114 A 1	
3115 D 1	
3121 A 1	
3122 B 1	
3124 C 2	
5101 B 1	
5102 C 2	
5107 B 2	
5108 B 2	
5110 D 2	
5111 D 1	
5112a D 1	
5112b D 2	
5112c D 2	
5113 B 1	
5101 A 1	
5102 A 1	
5103 D 1	
5104 D 1	
7101 D 2	
9102 A 1	
9029 A 2	



# ALIGNMENT

SK...	FREQUENCY	I/P	VARICON	ADJUST	O/P	SCOPE/METER
-------	-----------	-----	---------	--------	-----	-------------

## AM - IF

MW *	468kHz via 10nF	A	min.	5110 5109	1	↑ ↓ max.
------	--------------------	---	------	--------------	---	-------------

## AM - RF

MW * 530 - 1710kHz	512kHz 1635kHz 550kHz 1500kHz	B	max. min. Tune Tune	5108 C4 5113 C3	1	↑ ↓ max.
-----------------------	--	---	------------------------------	--------------------------	---	-------------

## FM - RF

FM 87.5-108MHz	87.35MHz @	C	max.	5102	1	↑ ↓ max.
	108.25MHz @		min.	C2		
	88MHz @		Tune	5101		
	106MHz @		Tune	C1		


\* Mod. 400Hz 30% @ ± 0.15MHz

## STEREO DECODER

SK...	FREQUENCY	I/P	VARICON	ADJUST	O/P	SCOPE/METER
FM STEREO	98MHz \$	C	Tune	3108	D	↑ ↓ 152±0.1kHz


\$ Without Pilot

Repeat ↑  
↓




## TUNER CIRCUIT DIAGRAM - FM/MW

2102 <sub>a</sub>	F 6	2101 <sub>d</sub>	E 3	2106	D 1	2120	F 5	2133	B 8	2137	C 9	2141	E 8	3107	F 6	3112	D 8	3121	F 7	5102	E 2	5112 <sub>a</sub>	A 3	6101	B 1	7101	C 4
2101 <sub>a</sub>	D 1	2102	B 1	2107	D 1	2121	E 7	2134	B 8	2138	B 9	2142	E 9	3108	E 6	3113	B 9	3124	D 9	5108	E 4	5112 <sub>b</sub>	A 4	6102	B 1	8102	B 10
2101 <sub>b</sub>	E 1	2103	B 1	2115	E 2	2122	F 6	2135	C 8	2139	C 9	2146	D 10	3110	B 8	3114	C 9			5109	A 2	5112 <sub>c</sub>	A 5	6103	B 9		
2101 <sub>c</sub>	C 1	2105	C 1	2116	E 2	2130	E 4	2136	C 9	2140	D 8	3106	F 5	3111	C 8	3115	A 10	5101	D 1	5110	A 5	5113	C 1	6104	D 10		




# TUNER COMPONENT LAYOUT - FM/MW



1103 A 2  
 2101 B 2  
 2102 D 1  
 2103 D 1  
 2105 C 1  
 2106 C 1  
 2107 B 1  
 2111 B 2  
 2115 B 2  
 2116 B 2  
 2120 D 2  
 2121 D 2  
 2122 D 2  
 2133 D 2  
 2134 D 2  
 2135 D 2  
 2136 D 1  
 2137 D 1  
 2138 D 1  
 2139 C 1  
 2140 C 2  
 2141 D 2  
 2142 D 1  
 2146 A 1  
 3106 D 2  
 3107 B 2  
 3108 C 2  
 3110 D 1  
 3111 D 1  
 3112 D 2  
 3113 A 1  
 3114 A 1  
 3115 D 1  
 3121 A 1  
 3124 C 2  
 5101 B 1  
 5102 C 2  
 5108 B 2  
 5110 D 2  
 5111 D 1  
 5112a D 1  
 5112b D 2  
 5112c D 2  
 5113 B 1  
 6101 A 1  
 6102 A 1  
 6103 D 1  
 6104 D 1  
 7101 D 2  
 9102 A 1  
 9106 A 1  
 9115 C 2  
 9116 C 2  
 9118 C 1  
 9121 A 1  
 9122 C 1  
 9123 D 1  
 9124 B 2  
 9125 C 2

1103 A 2  
2101 B 2  
2102 D 1  
2103 D 1  
2105 C 1  
2106 C 1  
2107 B 1  
2111 B 2  
2115 B 2  
2116 B 2  
2120 D 2  
2121 D 2  
2122 D 2  
2133 D 2  
2134 D 2  
2135 D 2  
2136 D 1  
2137 D 1  
2138 D 1  
2139 C 1  
2140 C 2  
2141 D 2  
2142 D 1  
2146 A 1  
3106 D 2  
3107 B 2  
3108 C 2  
3110 D 1  
3111 D 1  
3112 D 2  
3113 A 1  
3114 A 1  
3115 D 1  
3121 A 1  
3124 C 2  
5101 B 1  
5102 C 2  
5108 B 2  
5110 D 2  
5111 D 1  
5112a D 1  
5112b D 2  
5112c D 2  
5113 B 1  
6101 A 1  
6102 A 1  
6103 D 1  
6104 D 1  
7101 D 2  
8102 A 1  
9106 A 1  
9115 C 2  
9116 C 2  
9118 C 1  
9121 A 1  
9122 C 1  
9123 D 1  
9124 B 2  
9125 C 2




## IC SPECIFICATION


### IC SPECIFICATION

#### TEA5711(T) - AM/FM Stereo Radio Circuit


SYMBOL	PIN	DESCRIPTION
NC	1	not connected
AF-Lo	2	left channel audio output (output imp. = 5kΩ)
AF-Ro	3	right channel audio output (output imp. = 5kΩ)
PILFIL	4	pilot detector filter pin
FM-DEM	5	ceramic discriminator pin
IFGND	6	ground of IF, detector and MPX stages
FM-IF2i	7	second FM-IF input (input imp. = 330Ω)
VSTAB <sub>B</sub>	8	stabilized internal supply voltage (B)
FM-IF1o	9	first FM-IF output (output imp. = 330Ω)
AM-IF2 <sub>vo</sub>	10	input/output to IFT; output: current source
FM-IF1i	11	first FM-IF input (input imp. = 330Ω)
VSTABA	12	stabilized internal supply voltage (A)
FM-MIXER	13	output to ceramic IF filter (output imp. = 330Ω)
AM-MIXER	14	open-collector output to IFT
AM-IF1i	15	input from IFT or ceramic filter (input imp. = 3kΩ)
FM-RFi	16	FM-RF aerial input (input imp. = 3kΩ)
RFGND	17	FM-RF ground
AM-RFi	18	parallel tuned AM aerial circuit to ground (total input capacitance = 3pF)
RIPPLE	19	ripple capacitor pin
AM-AGC/FM-AFC	20	AGC/AFC capacitor pin
FM-RFo	21	parallel tuned FM-RF circuit to ground
SUBGND	22	substrate and RF ground
FM-OSC	23	parallel tuned FM-OSC circuit to ground
AM-OSC	24	parallel tuned AM-OSC circuit to ground
Vp	25	positive supply voltage
IND	26	signal level output
VCO/AM-FM SWITCH	27	VCO and switch terminal : open for AM ; ground for FM
AFo	28	AM/FM AF output (output imp. = 5kΩ)
MPXi	29	input for stereo decoder (input imp. = 150kΩ)
ST-LED	30	stereo indicator
LPF M/S	31	pin for loopfilter and mono/stereo switch
MUTE	32	mute pin












To Sheet 2



#### NOTES :

Replace items marked •


Item	Value
3714 / 3764	1k
3715 / 3763	10k
3700 / 3750	3k5
3716 / 3766	10k
3717 / 3767	1k
2715 / 2765	2n2


▽ For AZ8040 only  
○ For AZ8140 only  
✱ Provision Only

All voltages are measured in position CD - rec  
ans supply in DC mode.

Versions	9303	9310	1307
/01 & /21	×	×	✓
/17 & /37	✓	×	×
Others	×	✓	×




Fuse (Item 1306) Ratings:  
For -/17 1.6A  
Others 1.25A







1116	A 2	3610	I23
1220	B26	3611	I23
1251	B27	3612	H23
1270	B28	3613	H23
1291	J19	3614	H23
1305	K26	3615	H23
1306	J22	3616	H23
1307	J24	3617	H23
1320	D17	3618	H23
1350	L19	3619	H23
1350	K15	3620	H23
1350	B14	3621	H23
1350	E13	3622	H23
1350	M19	3623	H23
1350	L17	3624	H23
1350	E12	3625	H23
1350	K16	3626	H23
1350	L13	3627	H23
1350	D17	3628	H23
1350	L19	3629	H23
1350	K15	3630	H23
1350	B14	3631	H23
1350	E13	3632	H23
1350	M19	3633	H23
1350	L17	3634	H23
1350	E12	3635	H23
1350	K16	3636	H23
1350	L13	3637	H23
1350	D17	3638	H23
1350	L19	3639	H23
1350	K15	3640	H23
1350	B14	3641	H23
1350	E13	3642	H23
1350	M19	3643	H23
1350	L17	3644	H23
1350	E12	3645	H23
1350	K16	3646	H23
1350	L13	3647	H23
1350	D17	3648	H23
1350	L19	3649	H23
1350	K15	3650	H23
1350	B14	3651	H23
1350	E13	3652	H23
1350	M19	3653	H23
1350	L17	3654	H23
1350	E12	3655	H23
1350	K16	3656	H23
1350	L13	3657	H23
1350	D17	3658	H23
1350	L19	3659	H23
1350	K15	3660	H23
1350	B14	3661	H23
1350	E13	3662	H23
1350	M19	3663	H23
1350	L17	3664	H23
1350	E12	3665	H23
1350	K16	3666	H23
1350	L13	3667	H23
1350	D17	3668	H23
1350	L19	3669	H23
1350	K15	3670	H23
1350	B14	3671	H23
1350	E13	3672	H23
1350	M19	3673	H23
1350	L17	3674	H23
1350	E12	3675	H23
1350	K16	3676	H23
1350	L13	3677	H23
1350	D17	3678	H23
1350	L19	3679	H23
1350	K15	3680	H23
1350	B14	3681	H23
1350	E13	3682	H23
1350	M19	3683	H23
1350	L17	3684	H23
1350	E12	3685	H23
1350	K16	3686	H23
1350	L13	3687	H23
1350	D17	3688	H23
1350	L19	3689	H23
1350	K15	3690	H23
1350	B14	3691	H23
1350	E13	3692	H23
1350	M19	3693	H23
1350	L17	3694	H23
1350	E12	3695	H23
1350	K16	3696	H23
1350	L13	3697	H23
1350	D17	3698	H23
1350	L19	3699	H23
1350	K15	3700	H23
1350	B14	3701	H23
1350	E13	3702	H23
1350	M19	3703	H23
1350	L17	3704	H23
1350	E12	3705	H23
1350	K16	3706	H23
1350	L13	3707	H23
1350	D17	3708	H23
1350	L19	3709	H23
1350	K15	3710	H23
1350	B14	3711	H23
1350	E13	3712	H23
1350	M19	3713	H23
1350	L17	3714	H23
1350	E12	3715	H23
1350	K16	3716	H23
1350	L13	3717	H23
1350	D17	3718	H23
1350	L19	3719	H23
1350	K15	3720	H23
1350	B14	3721	H23
1350	E13	3722	H23
1350	M19	3723	H23
1350	L17	3724	H23
1350	E12	3725	H23
1350	K16	3726	H23
1350	L13	3727	H23
1350	D17	3728	H23
1350	L19	3729	H23
1350	K15	3730	H23
1350	B14	3731	H23
1350	E13	3732	H23
1350	M19	3733	H23
1350	L17	3734	H23
1350	E12	3735	H23
1350	K16	3736	H23
1350	L13	3737	H23
1350	D17	3738	H23
1350	L19	3739	H23
1350	K15	3740	H23
1350	B14	3741	H23
1350	E13	3742	H23
1350	M19	3743	H23
1350	L17	3744	H23
1350	E12	3745	H23
1350	K16	3746	H23
1350	L13	3747	H23
1350	D17	3748	H23
1350	L19	3749	H23
1350	K15	3750	H23
1350	B14	3751	H23
1350	E13	3752	H23
1350	M19	3753	H23
1350	L17	3754	H23
1350	E12	3755	H23
1350	K16	3756	H23
1350	L13	3757	H23
1350	D17	3758	H23
1350	L19	3759	H23
1350	K15	3760	H23
1350	B14	3761	H23
1350	E13	3762	H23
1350	M19	3763	H23
1350	L17	3764	H23
1350	E12	3765	H23
1350	K16	3766	H23
1350	L13	3767	H23
1350	D17	3768	H23
1350	L19	3769	H23
1350	K15	3770	H23
1350	B14	3771	H23
1350	E13	3772	H23
1350	M19	3773	H23
1350	L17	3774	H23
1350	E12	3775	H23
1350	K16	3776	H23
1350	L13	3777	H23
1350	D17	3778	H23
1350	L19	3779	H23
1350	K15	3780	H23
1350	B14	3781	H23
1350	E13	3782	H23
1350	M19	3783	H23
1350	L17	3784	H23
1350	E12	3785	H23
1350	K16	3786	H23
1350	L13	3787	H23
1350	D17	3788	H23
1350	L19	3789	H23
1350	K15	3790	H23
1350	B14	3791	H23
1350	E13	3792	H23
1350	M19	3793	H23
1350	L17	3794	H23
1350	E12	3795	H23
1350	K16	3796	H23
1350	L13	3797	H23
1350	D17	3798	H23
1350	L19	3799	H23
1350	K15	3800	H23
1350	B14	3801	H23
1350	E13	3802	H23
1350	M19	3803	H23
1350	L17	3804	H23
1350	E12	3805	H23
1350	K16	3806	H23
1350	L13	3807	H23
1350	D17	3808	H23
1350	L19	3809	H23
1350	K15	3810	H23
1350	B14	3811	H23
1350	E13	3812	H23
1350	M19	3813	H23
1350	L17	3814	H23
1350	E12	3815	H23
1350	K16	3816	H23
1350	L13	3817	H23
1350	D17	3818	H23
1350	L19	3819	H23
1350	K15	3820	H23
1350	B14	3821	H23
1350	E13	3822	H23
1350	M19	3823	H23
1350	L17	3824	H23
1350	E12	3825	H23
1350	K16	3826	H23
1350	L13	3827	H23
1350	D17	3828	H23
1350	L19	3829	H23
1350	K15	3830	H23
1350	B14	3831	H23
1350	E13	3832	H23
1350	M19	3833	H23
1350	L17	3834	H23
1350	E12	3835	H23
1350	K16	3836	H23
1350	L13	3837	H23
1350	D17	3838	H23
1350	L19	3839	H23
1350	K15	3840	H23
1350	B14	3841	H23
1350	E13	3842	H23
1350	M19	3843	H23
1350	L17	3844	H23
1350	E12	3845	H23
1350	K16	3846	H23
1350	L13	3847	H23
1350	D17	3848	H23
1350	L19	3849	H23
1350	K15	3850	H23
1350	B14	3851	H23
1350	E13	3852	H23
1350	M19	3853	H23
1350	L17	3854	H23
1350	E12	3855	H23
1350	K16	3856	H23
1350	L13	3857	H23
1350	D17	3858	H23
1350	L19	3859	H23
1350	K15	3860	H23
1350	B14	3861	H23
1350	E13	3862	H23
1350	M19	3863	H23
1350	L17	3864	H23
1350	E12	3865	H23
1350	K16	3866	H23
1350	L13	3867	H23
1350	D17	3868	H23
1350	L19	3869	H23
1350	K15	3870	H23
1350	B14	3871	H23
1350	E13	3872	H23
1350	M19	3873	H23
1350	L17	3874	H23
1350	E12	3875	H23
1350	K16	3876	H23
1350	L13	3877	H23
1350	D17	3878	H23
1350	L19	3879	H23
1350	K15	3880	H23
1350	B14	3881	H23
1350	E13	3882	H23
1350	M19	3883	H23
1350	L17	3884	H23
1350	E12	3885	H23
1350	K16	3886	H23
1350	L13	3887	H23
1350	D17	3888	H23
1350	L19	3889	H23
1350	K15	3890	H23
1350	B14	3891	H23
1350	E13	3892	H23
1350	M19	3893	H23
1350	L17	3894	H23
1350	E12	3895	H23
1350	K16	3896	H23
1350	L13	3897	H23
1350	D17	3898	H23
1350	L19	3899	H23
1350	K15	3900	H23

ADJUSTMENT TABLE (RCD1.2D)


CD-PART			
LASER CURRENT			
The APC (Automatic Power Control) for the laser diode is located on the disc drive and has been adjusted in the production line. Therefore for service purpose it is not intended to adjust the laser current.			
TRACKING BALANCE			
Service mode Step 2 Display shows $\epsilon^2$	TP40 & TP41	3805	Adjust to 0V DC offset

## HANDLING CHIP COMPONENTS


### GENERAL




### DISMOUNTING




### PRECAUTIONS



### MOUNTING




### EXAMPLES




COMBI BOARD COMPONENT LAYOUT

16 D 2	1901 B 9	2280 C 5	2574 D 9	2754 D 5	2812 B 4	2866 B 7	3272 C 5	3555 D 9	3709 D 3	3775 C 5	3831 A 3	3867 B 7	3934 A 5	7220 D 6	9203 D 6	9316 C 8	9702 D 3	9811 B 4	9835 C 3	A1 C 1	TP20 C 7	TP47 B 5
17 C 8	1912 D 9	2282 C 8	2580 B 8	2755 D 4	2815 A 4	2867 A 7	3277 D 6	3556 B 8	3713 B 7	3801 B 3	3832 B 3	3869 A 7	5300 C 1	7250 D 6	9204 D 6	9317 D 7	9703 A 8	9812 C 4	9836 A 8	B1 C 1	TP21 C 4	TP48 A 4
18 D 2	1913 A 9	2341 D 1	2610 C 7	2756 D 4	2817 A 5	2874 B 7	3280 C 9	3560 B 9	3714 C 7	3802 B 3	3833 B 3	3875 B 7	5770 C 3	7263 D 5	9205 C 5	9318 D 7	9704 D 4	9813 B 5	9837 A 8	C1 C 1	TP22 C 4	TP49 A 3
19 A 1	1914 D 9	2342 D 1	2611 C 6	2757 D 3	2818 A 4	2876 A 7	3281 C 8	3561 B 9	3716 C 3	3803 B 3	3834 A 3	3876 B 7	5851 B 6	7280 C 9	9206 D 6	9319 D 6	9705 C 4	9814 B 5	9838 A 8	D1 D 1	TP23 D 3	TP50 A 3
1116 C 7	1915 A 9	2343 D 1	2612 C 6	2758 D 4	2821 A 4	2877 A 7	3282 C 8	3570 C 9	3717 C 3	3805 C 3	3836 C 4	3877 A 7	5852 A 6	7520 B 9	9210 C 7	9320 C 5	9706 D 4	9815 C 5	9839 A 8	E1 D 1	TP24 D 5	TP51 A 3
1220 D 7	1916 A 9	2344 D 1	2613 C 6	2759 D 3	2825 A 4	2883 B 7	3300 C 2	3571 D 9	3750 C 5	3806 B 5	3837 C 4	3879 A 7	6250 D 7	7570 D 9	9211 A 2	9321 C 5	9707 D 4	9816 B 7	9840 A 8	TP1 A 2	TP27 D 3	TP52 A 4
1251 D 8	2222 D 5	2345 D 1	2614 C 6	2760 D 4	2826 A 4	2886 B 3	3301 C 2	3572 C 9	3751 C 4	3808 A 3	3838 B 5	3881 B 5	6280 C 9	7620 C 5	9212 A 2	9322 B 8	9708 D 4	9817 A 5	9841 A 8	TP2 A 1	TP28 C 4	TP53 A 5
1270 D 7	2223 D 5	2346 D 2	2615 C 6	2761 D 4	2831 A 3	2888 C 3	3302 C 2	3573 C 9	3752 D 5	3809 B 5	3840 B 4	3882 B 4	6281 B 9	7670 C 5	9220 D 6	9323 C 8	9710 D 4	9818 B 5	9842 A 8	TP3 D 7	TP29 C 3	conA D 6
1281 D 2	2224 D 5	2505 C 9	2616 C 7	2762 D 4	2832 A 3	2889 B 4	3303 C 2	3574 C 9	3753 D 5	3810 B 5	3841 A 3	3884 B 7	6282 C 9	7700 D 3	9270 D 8	9324 C 8	9711 C 6	9819 C 5	9843 A 8	TP4 D 8	TP30 D 5	conA D 6
1305 C 2	2225 D 5	2507 A 8	2700 C 4	2763 D 4	2833 A 3	2890 B 3	3304 C 2	3590 C 8	3754 D 4	3811 B 4	3842 A 3	3886 B 3	6283 D 5	7770 C 3	9300 D 7	9325 C 8	9713 C 6	9820 C 5	9844 A 8	TP5 D 8	TP31 C 6	conD D 6
1306 D 1	2226 D 6	2508 B 8	2701 D 3	2765 C 5	2834 A 3	2891 B 5	3305 D 2	3610 C 6	3755 D 3	3814 A 4	3843 A 3	3887 B 3	6341 D 1	7801 B 3	9301 C 6	9326 C 8	9714 C 7	9821 B 5	9845 B 8	TP6 D 6	TP32 D 8	conL D 6
1307 B 1	2227 D 6	2520 B 8	2702 D 3	2770 C 3	2836 C 4	2892 A 7	3500 A 7	3611 C 7	3757 D 3	3815 A 4	3844 A 3	3911 A 9	6342 D 1	7811 B 4	9302 C 7	9327 D 7	9715 C 4	9822 C 5	9846 A 6	TP7 C 7	TP33 D 8	conL D 6
1520 A 9	2228 D 6	2521 B 9	2703 D 3	2771 C 3	2837 B 4	2893 C 6	3501 C 8	3612 C 6	3758 D 4	3816 A 4	3845 A 3	3912 A 9	6343 D 1	7841 A 3	9303 C 1	9328 D 7	9716 D 4	9823 A 5	9847 B 9	TP8 D 7	TP34 D 8	conT D 6
1550 C 8	2229 C 6	2522 B 9	2704 D 3	2772 C 2	2838 B 4	2894 A 6	3503 A 8	3614 C 6	3759 D 3	3817 A 4	3846 A 4	3913 A 9	6344 D 1	7842 A 4	9305 C 7	9329 D 6	9720 D 3	9824 C 5	9849 B 8	TP9 C 8	TP35 C 8	8280 D 2
1770 C 4	2230 D 5	2523 B 9	2705 D 4	2773 C 2	2839 B 4	2913 A 6	3505 D 9	3620 C 5	3760 D 4	3818 A 4	3847 A 5	3914 A 9	6345 D 2	7851 B 6	9306 C 7	9502 B 9	9801 A 5	9825 A 6	9850 B 8	TP10 C 7	TP36 D 8	
1771 C 7	2256 D 6	2524 B 8	2706 D 4	2774 C 3	2840 B 4	2924 B 6	3506 B 8	3670 C 5	3761 D 4	3819 B 4	3848 A 5	3915 A 5	6609 C 6	7852 B 6	9307 C 7	9503 B 9	9802 A 3	9826 A 6	9851 B 9	TP11 B 7	TP37 B 8	
1772 C 8	2260 D 7	2555 C 9	2707 D 3	2775 C 3	2842 A 4	3220 D 5	3510 D 8	3700 D 5	3762 C 3	3821 A 4	3849 A 4	3916 A 9	6610 C 6	7861 B 7	9308 C 7	9507 C 8	9803 A 3	9827 A 6	9852 A 9	TP12 D 7	TP38 C 8	
1773 D 2	2261 D 7	2557 A 8	2708 D 3	2776 C 3	2843 A 4	3221 D 8	3520 B 9	3701 C 4	3763 B 7	3822 A 4	3850 A 5	3917 A 9	6611 C 6	7867 A 7	9309 C 7	9509 C 8	9804 B 5	9828 B 4	9853 A 5	TP13 C 3	TP40 C 4	
1775 D 3	2272 D 5	2558 B 7	2709 D 3	2802 B 3	2844 A 5	3222 D 5	3521 B 9	3702 D 5	3764 C 7	3823 A 4	3852 B 5	3918 A 9	6612 C 6	7877 A 7	9310 B 3	9511 B 8	9805 B 3	9829 A 6	9854 B 9	TP14 C 7	TP41 A 3	
1780 C 4	2273 C 5	2560 B 9	2715 D 5	2803 A 5	2851 B 5	3227 D 6	3522 B 8	3703 D 3	3766 C 4	3824 A 3	3853 B 5	3921 A 6	6911 A 5	7901 A 6	9311 C 1	9512 B 8	9806 B 3	9830 A 6	9855 B 7	TP15 D 7	TP42 A 5	
1801 B 3	2274 D 5	2570 C 9	2750 C 4	2804 B 3	2852 C 6	3263 D 5	3523 B 8	3704 D 3	3767 C 4	3825 A 4	3854 B 6	3922 A 6	6912 A 5	7902 C 9	9312 C 1	9513 B 8	9807 B 3	9831 B 6	9856 B 7	TP16 B 7	TP43 A 4	
1802 A 3	2276 D 6	2571 D 9	2751 D 4	2805 C 3	2854 B 5	3265 D 5	3524 B 9	3705 D 3	3771 C 3	3826 A 3	3857 B 7	3931 A 5	6920 B 5	7931 A 5	9313 C 2	9514 B 8	9808 B 5	9832 B 6	9857 A 6	TP17 B 7	TP44 B 8	
1803 A 5	2277 D 6	2572 C 9	2752 D 5	2806 B 3	2859 B 6	3270 C 5	3551 C 8	3707 D 3	3772 C 2	3829 B 3	3865 B 7	3932 A 5	6921 A 6	9201 C 4	9314 D 1	9515 B 8	9809 B 4	9833 A 7	9858 C 5	TP18 B 7	TP45 B 8	
1804 A 5	2278 D 6	2573 C 9	2753 D 3	2811 B 5	2864 B 7	3271 D 8	3553 A 7	3708 D 3	3773 C 3	3830 A 3	3866 B 7	3933 A 5	6922 C 6	9202 D 6	9315 B 8	9701 D 3	9810 B 4	9834 A 6	9859 C 6	TP19 D 7	TP46 C 4	





TAPEDECK EXPLODED VIEW




TAPEDECK PARTSLIST

27	4822 358 31231	Belt FF
67	4822 402 61418	Arm Pinch
68	4822 528 70785	Roller Pinch
84	4822 402 61419	Erase Head Arm
85	4822 249 40296	Erase Head
88	4822 249 10425	R/PF Head
101	4822 361 21698	Assy Motor
111	4822 278 90752	Leaf Switch
114	4822 278 90721	Leaf Switch

Note : Only the parts mentioned in this list are normal service spare parts.

SET EXPLODED VIEW



# SET MECHANICAL PARTSLIST

202	4822 276 13079	Latch Switch
203	4822 529 10257	Damper Assy
208	4822 532 61104	Distance-Holder
209	4822 532 61103	Damper
211	4822 303 30298	Telescopic Aerial
214	4822 410 63014	Button Set CD 1
215	4822 410 63015	Button Set CD 2
218	4822 410 63016	Button Record
219	4822 410 63022	Button Play
220	4822 410 63017	Button REW
221	4822 410 63018	Button FWD
222	4822 410 63019	Button Stop
223	4822 410 63021	Button Pause
231	4822 403 30809	Bracket Record
238	4822 411 61955	Knob Band
240	4822 454 12921	Sticker Dialscale /00/05/20
240	4822 454 12928	Sticker Dialscale /37
240	4822 333 30228	Sticker Dialscale /21/41
250	4822 423 41252	Cabinet Rear
251	4822 462 40683	Plate (foot)
253	4822 492 52299	Spring-Battery
255	4822 492 51733	Spring Compression
259	4822 404 10881	Bracket Power
265	4822 443 64079	Door CD/Cass Assy
266	4822 450 62179	Lens Cass/CD
267	4822 535 60096	Disc
268	4822 532 51871	Pressure Ring Assy
271	4822 492 71463	Spring CD
275	4822 411 61956	Knob Mode
276	4822 413 51466	Knob Volume
277	4822 492 51374	Ring
278	4822 454 12932	Plate Voltage /21/41
280	4822 423 51163	Panel Front
280 *	4822 423 51167	Panel Front /21/41
280 *	4822 423 51169	Panel Front /37
281	4822 464 70628	Frame Loudspeaker
281	4822 464 70634	Frame Loudspeaker /21/41/37
287	4822 498 10505	Handle
290	4822 423 41251	Door Battery
293	4822 404 10882	Bracket LCD
385	4822 321 10831 Δ	Mains Cord
385	4822 321 10918 Δ	Main Cord /05
385	4822 321 10883 Δ	Main Cord /37
	4822 736 21933	IFU
	4822 736 21967	IFU /21/41
	4822 736 22002	IFU /37

Note : Only the parts mentioned in this list are normal service spare parts.

\* See Annex on Tuner Board Rework.

# LIST OF SCREWS

213	PLASTITE TORX SCR ST ZN 3 X12
225	PLASTITE TORX SCR ST ZN 3 X16
227	PLASTITE TORX SCR ST ZN 3 X12
228	PLASTITE TORX SCR ST ZN 2 X16
229	PLASTITE TORX SCR ST ZN 2 X10
230	PLASTITE TORX SCR ST ZN 3 X12
236	PLASTITE TORX SCR ST ZN 3 X12
241	PLASTITE TORX SCR ST ZN 3 X16
242	TRUSS SCR M2.6X6X0.45P
243	LOCK WASH D2.8
245	PLAST TORX SCR ST ZN WASH 3X12
254	PLAST TORX SCR ST ZN WASH 3X12
257	PLAST TORX SCR ST ZN WASH 3X12
260	PLAST TORX SCR ST ZN WASH 3X16
261	PLAST TORX SCR ST ZN WASH 3X16
273	PLASTITE TORX SCR ST ZN 3 X12
283	PLASTITE TORX SCR ST ZN 3 X12
285	PLASTITE TORX SCR ST ZN 3 X25
286	PLASTITE TORX SCR ST ZN 3 X16
295	PLASTITE TORX SCR ST ZN 3 X16
298	PLASTITE TORX SCR ST ZN 3 X16

# TUNER BOARD – FM/LW/MW

## MISCELLANEOUS

1102 4822 277 21626 Switch Slide 6P3T



2101	4822 125 30027	Polyvaricon
2102	4822 126 12675	15pF 50V 5%
2103	4822 122 32764	4n7 20%
2105	4822 124 80678	10μF 50V 20%
2106	4822 124 80678	10μF 50V 20%
2107	4822 126 12304	27pF 50V 5%
2108	4822 125 50045	Trimmer 1P8-22P
2111	4822 126 12414	20pF 5%
2115	4822 122 32147	22pF 50V 5%
2116	4822 126 12809	2.2pF 50V 0.5%
2120	4822 124 40433	47μF 16V 20%
2121	4822 124 40746	0.22μF 63V 20%
2122	4822 126 12671	330pF 50V 10%
2123	4822 125 50062	Trimmer 1.4p-10pF 250V
2127	5322 121 54058	110pF 630V 1%
2130	4822 126 12337	3.9pF 50V 5%
2133	4822 124 22467	2.2μF 50V 20%
2134	4822 124 80141	10nF 50V 10%
2135	4822 124 80141	10nF 50V 10%
2136	4822 126 12672	4.7nF 50V 10%
2137	4822 126 12672	4.7nF 50V 10%
2138	4822 124 40246	4.7μF 63V 20%
2139	4822 124 40246	4.7μF 63V 20%
2140	4822 124 40242	1μF 63V 20%
2141	4822 124 40239	0.47μF 50V 20%
2142	4822 124 40239	0.47μF 50V 20%
2146	4822 124 80141	10nF 50V 10%
2149	4822 126 11183	1nF 50V 10%
2150	4822 126 13093	22pF 50V 5%



3106	4822 050 13309	33Ω 5%
3107	4822 050 18203	82K 5%
3108	4822 101 11259	Trimmer 50k
3110	4822 050 11802	1k8 5%
3111	4822 050 11802	1k8 5%
3112	4822 050 14702	4k7 5%
3113	4822 050 11004	100K 5%
3114	4822 050 11004	100K 5%
3115	4822 050 14704	470K 5%
3121	4822 050 11003	10K 5%
3122	4822 116 52182	15Ω 5%
3124	4822 116 52252	180K 5%



5101	4822 157 70513	Coil FM
5102	4822 156 30947	RF Coil 1.5 T
5107	4822 157 70144	Coil-M/O 270μH Green
5108	4822 157 70107	Coil-M/O 270μH Red
5109	4822 157 70499	IFT-AM 7MM WHT
5110	4822 156 11146	IFT-AM 7MM BLK
5112	4822 242 81154	Filter Kit 10.7MHz
5113	4822 158 60627	Bar-Coil Assy MW/LW






6101	4822 130 30621	1N4148
6102	4822 130 30621	1N4148
6103	4822 130 30621	1N4148
6104	4822 130 30621	1N4148






7101	4822 209 32746	TEA5711T/N2
------	----------------	-------------

Note: Only the parts mentioned in this list are normal service spare parts.


TUNER BOARD – FW/MW


MISCELLANEOUS		
1102	4822 277 21587	SW-Slide 2P2T
		
2101	4822 125 30027	Polyvaricon
2102	4822 126 12675	15pF 50V 5%
2103	4822 122 32764	4n7 20%
2105	4822 124 80678	10µF 50V 20%
2106	4822 124 80678	10µF 50V 20%
2107	4822 126 12814	24pF 5%
2115	4822 122 32147	22pF 50V 5%
2116	4822 126 12809	2.2pF 50V 0.5%
2120	4822 124 40433	47µF 16V 20%
2121	4822 124 40746	0.22µF 63V 20%
2122	4822 126 12671	330pF 50V 10%
2130	4822 126 12229	8.2pF 50V 0.25%
2133	4822 124 22467	2.2µF 50V 20%
2134	4822 124 80141	10nF 50V 10%
2135	4822 124 80141	10nF 50V 10%
2136	4822 126 12672	4.7nF 50V 10%
2137	4822 126 12672	4.7nF 50V 10%
2138	4822 124 41398	1µF 63V 20%
2139	4822 124 41398	1µF 63V 20%
2140	4822 124 40242	1µF 50V 20%
2141	4822 124 40239	0.47µF 50V 20%
2142	4822 124 40239	0.47µF 50V 20%
2146	4822 124 80141	10nF 50V 10%
2149	4822 126 11183	1nF 50V 10%
		
3106	4822 050 13309	33Ω 5%
3107	4822 050 18203	82k 5%
3108	4822 101 11259	Trimmer 50k
3110	4822 050 11802	1k8 5%
3111	4822 050 11802	1k8 5%
3112	4822 116 52256	2k2 5%
3113	4822 050 11004	100K 5%
3114	4822 050 11004	100K 5%
3115	4822 050 14704	470K 5%
3121	4822 050 11003	10K 5%
3124	4822 116 52252	180K 5%
		
5101	4822 157 70513	Coil FM
5102	4822 156 30947	RF Coil 1.5 T
5108	4822 157 70107	Coil-M/O 270µH RED
5109	4822 157 70499	IFT-AM 7MM WHT

		
5110	4822 156 11146	IFT-AM 7MM BLK
5112	4822 242 81535	Cerkit filter 10.7MHz
5113	4822 158 60621	Bar Coil Assy MW 10:60
		
6101	4822 130 30621	1N4148
6102	4822 130 30621	1N4148
6103	4822 130 30621	1N4148
6104	4822 130 30621	1N4148
		
7101	4822 209 32746	TEA5711T/N2

Note: Only the parts mentioned in this list are normal service spare parts.

COMBI BOARD

MISCELLANEOUS		
1305	4822 265 20287	△ Mains Socket
1305	4822 265 30986	△ Mains Socket /17/37
1306	4822 070 31252	△ Fuse T1.25A 250V
1306	5322 253 30203	△ Fuse T1.6A 250V /17/37
1307	4822 272 10366	△ Voltage Selector /21/41
1550	4822 277 30689	Slide Switch
1780	4822 277 20594	Slide Switch
1901	4822 130 91311	LCD LH6168-C
1912	4822 276 13114	Push Switch
1913	4822 276 13114	Push Switch
1914	4822 276 13114	Push Switch
1915	4822 276 13114	Push Switch
1916	4822 276 13114	Push Switch
		
2222	4822 124 40242	1µF 20% 63V
2223	4822 122 33197	1nF 10% 50V
2224	4822 124 41643	100µF 20% 16V
2225	4822 124 40196	220µF 20% 16V
2226	4822 124 40433	47µF 20% 25V
2227	4822 121 41854	150nF 5% 63V
2228	4822 124 41997	470µF 10V
2229	4822 122 33307	10nF 5% 50V
2230	4822 122 33169	680pF 10% 50V
2256	4822 124 42119	4700µF 20% 25V
2261	4822 124 41643	100µF 20% 16V
2272	4822 124 40242	1µF 20% 63V
2273	4822 122 33197	1nF 10% 50V
2274	4822 124 41643	100µF 20% 16V
2276	4822 124 40433	47µF 20% 25V
2277	4822 121 41854	150nF 5% 63V
2278	4822 124 41997	470µF 10V
2280	4822 122 33169	680pF 10% 50V
2282	4822 124 41643	100µF 20% 16V
2341	4822 122 33307	10nF 5% 50V
2342	4822 122 33307	10nF 5% 50V
2343	4822 122 33307	10nF 5% 50V
2344	4822 122 33307	10nF 5% 50V
2345	4822 121 51379	100nF 5%
2507	4822 126 12878	1.5nF 10% 16V
2508	5322 121 42465	68nF 5% 63V
2557	4822 126 12878	1.5nF 10% 16V
2558	5322 121 42465	68nF 5% 63V
2610	5322 124 41431	22µF 20% 35V
2611	5322 124 41431	22µF 20% 35V
2612	4822 124 40246	4.7µF 20% 63V
2613	4822 126 11714	4.7nF 20%
2614	4822 126 11714	4.7nF 20%
2615	4822 126 11714	4.7nF 20%
2616	4822 126 12147	22nF 10% 25V

		
2700	4822 126 12878	1.5nF 10% 16V
2701	4822 126 12147	22nF 10% 25V
2702	4822 124 40433	47µF 20% 25V
2703	4822 126 12147	22nF 10% 25V
2704	4822 121 51305	15nF 10% 50V
2705	4822 124 40242	1µF 20% 63V
2706	4822 126 12878	1.5nF 10% 16V
2707	4822 122 33519	470pF 10% 50V
2708	4822 124 41643	100µF 20% 16V
2709	4822 122 33519	470pF 10% 50V
2715	4822 126 12339	2.2nF 10%
2750	4822 126 12878	1.5nF 10% 16V
2751	4822 126 12147	22nF 10% 25V
2752	4822 124 40433	47µF 20% 25V
2753	4822 126 12147	22nF 10% 25V
2754	4822 121 51305	15nF 10% 50V
2755	4822 124 40242	1µF 20% 63V
2756	4822 126 12878	1.5nF 10% 16V
2757	4822 122 33519	470pF 10% 50V
2758	4822 124 41643	100µF 20% 16V
2759	4822 122 33519	470pF 10% 50V
2760	5322 124 41431	22µF 20% 35V
2761	4822 124 40196	220µF 20% 16V
2762	4822 124 40248	10µF 20% 63V
2763	4822 121 43526	47nF 5% 250V
2765	4822 126 12339	2.2nF 10%
2770	4822 124 40242	1µF 20% 63V
2771	4822 122 33197	1nF 10% 50V
2774	4822 121 51304	10nF 10% 50V
2775	4822 126 11714	4.7nF 20%
2776	4822 126 12147	22nF 10% 25V
2802	4822 122 33069	33pF 5% 50V
2803	4822 122 10574	1.2nF 10% 16V
2804	4822 126 13098	5.6nF 20% 16V
2805	4822 126 10053	180pF 10%
2806	5322 121 42465	68nF 5% 63V
2811	4822 124 40248	10µF 20% 63V
2812	4822 124 40246	4.7µF 20% 63V
2815	4822 124 40239	0.47µF 20% 63V
2817	4822 124 40239	0.47µF 20% 63V
2818	4822 124 41643	100µF 20% 16V
2821	4822 121 51256	39nF 10% 50V
2825	4822 124 40239	0.47µF 20% 63V
2826	4822 121 51256	39nF 10% 50V
2831	5322 121 42465	68nF 5% 63V
2832	4822 124 40242	1µF 20% 63V
2833	4822 126 11714	4.7nF 20%
2834	4822 126 12147	22nF 10% 25V
2836	4822 126 11714	4.7nF 20%
2837	4822 124 40239	0.47µF 20% 63V
2838	4822 126 12339	2.2nF 10%
2839	4822 126 12882	100nF +80-20% 50V



## COMBI BOARD



2840	4822 126 12882	100nF +80-20% 50V
2842	4822 124 40244	2.2μF 20% 63V
2843	4822 124 23794	470μF 20% 16V
2844	4822 124 40433	47μF 20% 25V
2851	4822 122 10459	560pF 10% 50V
2852	4822 121 43396	120nF 5% 63V
2854	4822 126 12878	1.5nF 10% 16V
2859	4822 121 42408	220nF 5% 63V
2864	4822 124 40242	1μF 20% 63V
2866	4822 126 12148	2.7nF 10%
2867	4822 126 10003	33nF 30% 50V
2874	4822 124 40242	1μF 20% 63V
2876	4822 126 12148	2.7nF 10%
2877	4822 126 10003	33nF 30% 50V
2883	4822 124 41997	470μF 10V
2886	4822 121 51252	470nF 5% 63V
2888	4822 124 40433	47μF 20% 25V
2889	4822 124 40433	47μF 20% 25V
2890	4822 121 51252	470nF 5% 63V
2891	4822 124 40196	220μF 20% 16V
2892	4822 122 33197	1nF 10% 50V
2893	4822 121 51387	10nF 20% 16V
2913	4822 126 12147	22nF 10% 25V
2924	4822 124 40746	0.22μF 20% 63V



3220	4822 116 52206	120Ω 5% 0.5W
3222	4822 116 52224	470Ω 5% 0.5W
3227	4822 050 24708	4Ω 7 1% 0.6W
3263	4822 116 52234	100k 5% 0.5W
3265	4822 116 52251	18k 5% 0.5W
3270	4822 116 52206	120Ω 5% 0.5W
3272	4822 116 52224	470Ω 5% 0.5W
3277	4822 050 24708	4Ω 7 1% 0.6W
3500	4822 102 10417	Potm 50kB x 2
3501	4822 116 52283	4k7 5% 0.5W
3503	4822 116 52283	4k7 5% 0.5W
3506	4822 116 52296	6k8 5% 0.5W
3551	4822 116 52283	4k7 5% 0.5W
3553	4822 116 52283	4k7 5% 0.5W
3556	4822 116 52296	6k8 5% 0.5W
3610	4822 116 52244	15k 5% 0.5W
3611	4822 116 52244	15k 5% 0.5W
3612	4822 116 52244	15k 5% 0.5W
3614	4822 116 52244	15k 5% 0.5W
3620	4822 116 52233	10k 5% 0.5W
3670	4822 116 52233	10k 5% 0.5W
3700	4822 116 52269	3k3 5% 0.5W
3701	4822 116 52238	12k 5% 0.5W
3702	4822 116 52219	330Ω 5% 0.5W




3703	4822 116 52303	8k2 5% 0.5W
3704	4822 116 52197	56Ω 5% 0.5W
3705	4822 116 52224	470Ω 5% 0.5W
3707	4822 116 52175	100Ω 5% 0.5W
3708	4822 116 52233	10k 5% 0.5W
3709	4822 116 52239	120k 5% 0.5W
3713	4822 116 52233	10k 5% 0.5W
3714	4822 050 11002	1k 1% 0.4W
3716	4822 116 52233	10k 5% 0.5W
3717	4822 050 11002	1k 1% 0.4W
3750	4822 116 52269	3k3 5% 0.5W
3751	4822 116 52238	12k 5% 0.5W
3752	4822 116 52219	330Ω 5% 0.5W
3753	4822 116 52303	8k2 5% 0.5W
3754	4822 116 52197	56Ω 5% 0.5W
3755	4822 116 52224	470Ω 5% 0.5W
3757	4822 116 52175	100Ω 5% 0.5W
3758	4822 116 52233	10k 5% 0.5W
3759	4822 116 52239	120k 5% 0.5W
3760	4822 111 30893	4M7 5% 0.2W
3761	4822 116 52195	47Ω 5% 0.5W
3762	4822 116 52245	150k 5% 0.5W
3763	4822 116 52233	10k 5% 0.5W
3764	4822 116 52303	8k2 5% 0.5W
3766	4822 116 52233	10k 5% 0.5W
3767	4822 050 11002	1k 1% 0.4W
3771	4822 116 52245	150k 5% 0.5W
3772	4822 116 52176	10Ω 5% 0.5W
3773	4822 116 52206	120Ω 5% 0.5W
3775	4822 116 52284	47k 5% 0.5W
3801	4822 116 52303	8k2 5% 0.5W
3802	4822 116 52283	4k7 5% 0.5W
3803	4822 116 52303	8k2 5% 0.5W
3805	4822 100 11213	22k 30%lin 0.1W
3808	4822 116 81223	1M2 5%
3809	4822 116 52233	10k 5% 0.5W
3810	4822 116 52271	33k 5% 0.5W
3811	4822 116 52284	47k 5% 0.5W
3814	4822 116 52252	180k 5% 0.5W
3815	4822 116 52276	3k9 5% 0.5W
3816	4822 116 52256	2k2 5% 0.5W
3817	4822 116 52197	56Ω 5% 0.5W
3818	4822 050 11002	1k 1% 0.4W
3819	4822 116 52292	560k 5% 0.5W
3821	4822 116 52175	100Ω 5% 0.5W
3822	4822 116 52233	10k 5% 0.5W
3823	4822 116 52234	100k 5% 0.5W
3824	4822 116 52296	6k8 5% 0.5W
3825	4822 116 52256	2k2 5% 0.5W
3828	4822 116 52249	1k8 5% 0.5W
3829	4822 116 81682	2M2 5% 0.5W
3830	4822 116 52238	12k 5% 0.5W



3831	4822 116 52304	82k 5% 0.5W
3832	4822 116 52244	15k 5% 0.5W
3833	4822 116 52257	22k 5% 0.5W
3834	4822 116 52234	100k 5% 0.5W
3836	4822 116 52257	22k 5% 0.5W
3837	4822 116 52269	3k3 5% 0.5W
3840	4822 116 52284	47k 5% 0.5W
3841	4822 116 52233	10k 5% 0.5W
3842	4822 116 52222	390Ω 5% 0.5W
3843	4822 116 52233	10k 5% 0.5W
3844	4822 116 52231	820Ω 5% 0.5W
3845	4822 116 52233	10k 5% 0.5W
3846	4822 116 52224	470Ω 5% 0.5W
3847	4822 116 52257	22k 5% 0.5W
3848	4822 116 52257	22k 5% 0.5W
3849	4822 116 52224	470Ω 5% 0.5W
3850	4822 116 52224	470Ω 5% 0.5W
3852	4822 116 52228	680Ω 5% 0.5W
3853	4822 116 52271	33k 5% 0.5W
3854	4822 116 52277	39k 5% 0.5W
3857	4822 116 52256	2k2 5% 0.5W
3865	4822 116 52284	47k 5% 0.5W
3866	4822 050 11002	1k 1% 0.4W
3867	4822 116 52224	470Ω 5% 0.5W
3869	4822 116 52233	10k 5% 0.5W
3875	4822 116 52284	47k 5% 0.5W
3876	4822 050 11002	1k 1% 0.4W
3877	4822 116 52224	470Ω 5% 0.5W
3879	4822 116 52233	10k 5% 0.5W
3881	4822 116 52233	10k 5% 0.5W
3884	4822 116 52175	100Ω 5% 0.5W
3886	4822 052 10478 Δ	4Ω 7 5% 0.33W
3887	4822 050 11002	1k 1% 0.4W
3911	4822 116 52283	4k7 5% 0.5W
3912	4822 116 52283	4k7 5% 0.5W
3913	4822 116 52283	4k7 5% 0.5W
3914	4822 116 52283	4k7 5% 0.5W
3915	4822 116 52269	3k3 5% 0.5W
3916	4822 116 52284	47k 5% 0.5W
3917	4822 116 52284	47k 5% 0.5W
3918	4822 116 52284	47k 5% 0.5W
3921	4822 116 52284	47k 5% 0.5W
3922	4822 116 52234	100k 5% 0.5W
3931	4822 050 24708	4Ω 7 1% 0.6W
3932	4822 116 52207	1k2 5% 0.5W
3933	4822 116 52249	1k8 5% 0.5W
3934	4822 116 52231	820Ω 5% 0.5W



5770	4822 156 20946	Osc Coil 100kHz
------	----------------	-----------------



5851	4822 242 73557	CST8.46MTW-TF01
5852	4822 157 51195	1μH 20%




6250	5322 130 30684	1N4002
6283	4822 130 30621	1N4148
6341	5322 130 30684	1N4002
6342	5322 130 30684	1N4002
6343	5322 130 30684	1N4002
6344	5322 130 30684	1N4002
6609	4822 130 30621	1N4148
6610	4822 130 30621	1N4148
6611	4822 130 30621	1N4148
6612	4822 130 30621	1N4148
6911	4822 130 30621	1N4148
6912	4822 130 30621	1N4148
6920	4822 130 30621	1N4148
6921	4822 130 30621	1N4148
6922	5322 130 30684	1N4002



7220	4822 209 70372	TA7769P
7250	4822 209 12335	L4941
7263	5322 130 60068	TBC558C
7620	4822 130 44196	TBC548C
7670	4822 130 44196	TBC548C
7700	4822 209 32918	AN7318S
7770	4822 130 40937	TBC548B
7801	4822 209 72814	M51567P
7811	4822 209 72815	M51564P
7841	4822 209 32852	TDA7073A/N2
7842	4822 209 32852	TDA7073A/N2
7851	4822 209 62371	M50427AFP
7852	4822 209 70422	MN4264-15
7861	4822 209 32421	TDA1311A/N2
7867	4822 130 44196	TBC548C
7877	4822 130 44196	TBC548C
7901	4822 209 33073	M68HC05P4
7902	5322 209 10421	HEF4094BP
7931	4822 130 41246	BC327-25

Note : Only the parts mentioned in this list are normal service spare parts.

MISCELLANEOUS PARTSLIST

MISCELLANEOUS		
1730	4822 691 20904	Tape Deck YS37Z
1805	4822 276 12163	Leaf-SW LSA-1119G
1840	4822 691 20768	RCD-1.2D Drive Assy
5225	4822 240 30689	Loudspeaker 6Ω 2W
5275	4822 240 30689	Loudspeaker 6Ω 2W
		
5300	4822 146 31319	Transformer

Note : Only the parts mentioned in this list are normal service spare parts.

GB WARNING

All ICs and many other semi-conductors are susceptible to electrostatic discharges (ESD). Careless handling during repair can reduce life drastically.  
When repairing, make sure that you are connected with the same potential as the mass of the set via a wrist wrap with resistance. Keep components and tools also at this potential.

ESD



NL WAARSCHUWING

Alle IC's en vele andere halfgeleiders zijn gevoelig voor electrostatische ontladingen (ESD).  
Onzorgvuldig behandelen tijdens reparatie kan de levensduur drastisch doen verminderen. Zorg ervoor dat u tijdens reparatie via een polsband met weerstand verbonden bent met hetzelfde potentiaal als de massa van het apparaat.  
Houd componenten en hulpmiddelen ook op hetzelfde potentiaal.

F ATTENTION

Tous les IC et beaucoup d'autres semi-conducteurs sont sensibles aux décharges statiques (ESD).  
Leur longévité pourrait être considérablement écourtée par le fait qu'aucune précaution n'est prise à leur manipulation.  
Lors de réparations, s'assurer de bien être relié au même potentiel que la masse de l'appareil et enfiler le bracelet serti d'une résistance de sécurité.  
Veiller à ce que les composants ainsi que les outils que l'on utilise soient également à ce potentiel.

D WARNUNG

Alle ICs und viele andere Halbleiter sind empfindlich gegenüber elektrostatischen Entladungen (ESD).  
Unvorsorgfällige Behandlung im Reparaturfall kan die Lebensdauer drastisch reduzieren.  
Veranlassen Sie, dass Sie im Reparaturfall über ein Pulsarmband mit Widerstand verbunden sind mit dem gleichen Potential wie die Masse des Gerätes.  
Bauteile und Hilfsmittel auch auf dieses gleiche Potential halten.

I AVVERTIMENTO

Tutti IC e parecchi semi-conduttori sono sensibili alle scariche statiche (ESD).  
La loro longevità potrebbe essere fortemente ridatta in caso di non osservazione della più grande cauzione alla loro manipolazione.  
Durante le riparazioni occorre quindi essere collegato allo stesso potenziale che quello della massa dell'apparecchio tramite un braccialetto a resistenza.  
Assicurarsi che i componenti e anche gli utensili con quali si lavora siano anche a questo potenziale.

"Pour votre sécurité, ces documents doivent être utilisés par des spécialistes agréés, seuls habilités à réparer votre appareil en panne".

GB

Safety regulations require that the set be restored to its original condition and that parts which are identical with those specified, be used:

NL

Veiligheidsbepalingen vereisen, dat het apparaat bij reparatie in zijn oorspronkelijke toestand wordt teruggebracht en dat onderdelen, identiek aan de gespecificeerde, worden toegepast.

F

Les normes de sécurité exigent que l'appareil soit remis à l'état d'origine et que soient utilisés les pièces de rechange identiques à celles spécifiées.


D

Bei jeder Reparatur sind die geltenden Sicherheitsvorschriften zu beachten. Der Originalzustand des Geräts darf nicht verändert werden; für Reparaturen sind Original-Ersatzteile zu verwenden.

I

Le norme di sicurezza esigono che l'apparecchio venga rimesso nelle condizioni originali e che siano utilizzati i pezzi di ricambio identici a quelli specificati.

"After servicing and before returning set to customer perform a leakage current measurement test from all exposed metal parts to earth ground to assure no shock hazard exist. The leakage current must not exceed 0.5mA."



GB Warning !

Invisible laser radiation when open.  
Avoid direct exposure to beam.

S Varning !

Osynlig laserstrålning när apparaten är öppnad och spärren är urkopplad. Betrakta ej strålen.

SF Varoitus !

Avatussa laitteessa ja suojalukituksen ohitettaessa olet alttiina näkymättömälle laserisäteilylle. Älä katso säteeseen!

DK Advarse !


Usynlig laserstråling ved åbning når sikkerhedsafbrydere er ude af funktion. Undgå udsættelse for stråling.

## TUNER BOARD REWORK

### For Sets with 2 band (FM/AM) Tuner only

Due to wrong printing of the Panel Front Assy ("FM" and "AM" are reverse) the following rework were made on the production floor for sets with SV code "00" :

1. Jumper between pin 1 and 6 of item 1102
2. Cut copper track between pin 2 and 5 of item 1102



Only Panel Front Assy with the correct printing will be in stock. In case there is a need to change the Panel Front Assy (pos. 280, 4822 423 51167, 4822 423 51169) for sets with SV code "00", do the following :

1. Remove the jumper.
2. Join pin 2 and 5 of item 1102